

Nanocomposite Materials, Properties, and Industrial Applications

Posted on January 10, 2020

Introduction

Nanocomposite (polymeric nanocomposite) is a multi-component material consisting of a plastic polymer matrix and filler of organ-modified nano clay, which has new, improved properties. The statement that the global polymer-nanocomposites market would grow by 24% by 2019 was a historical forecast whose target date has passed. According to analysts, the following factors will affect the growth of the world market of polymer nanocomposites: High demand from the automotive industry, tougher environmental regulations on emissions of harmful substances by road, growth of consumption from the production of clay nanocomposites on a polymer basis; and the general growth of demand from other segments of use.



Analysis

The nanocomposite is a multiphase solid material where at least the dimensions of one phase in one direction are less than one hundred nanometers. That phase, which is in the predominant quantity, is called the nanocomposite matrix. Nanocomposites can also include materials with a regular alternation of nano-sized phases. The mechanical, electrical, thermal, optical, and other characteristics of nanocomposites differ markedly from those of ordinary composite materials made from the same basic substances. Nanocomposites can be classified according to the following main parameters: matrix material, internal structure architecture, fundamental properties of the nanocomposite (conductive, refractory, magnetic, etc.)

Most often, polymers, metals, silicates, or ceramics are used as the base phase for a nanocomposite. There are natural (natural) and artificially synthesized nanocomposites.

It is noteworthy that the properties of nanocomposites are not additive to the properties of each phase. The nanoscales of one of the phases cause an increased energy reserve of its particles; they have completely different properties from the massive substance. The properties of nanocomposites as a whole can radically differ from the properties of each of its components. Also, the properties of nanocomposites depend on the quantitative content of the nanophase in the sample. Also, the properties of nanocomposites strongly depend on the architecture of the composite and the chemical nature of its constituent phases. The change in the shape and arrangement of nanoparticles can

greatly alter the properties of nanocomposites. It is possible to create such nanocomposites whose properties will not be isotropic; that is, they will differ in different directions. Using the above-described features, it is possible to pre-program and obtain nanocomposites with the necessary properties.



Historical Background

To synthesize nanocomposite materials with specified properties and polyfunctional activity, synthesis of metal nanoparticles in inverse micelles is carried out using the radiation-chemical and chemical methods for obtaining nanostructures, metallic nanoparticles of Ag, Fe, Zn, Pd, Pt, Ni, etc., and bimetallic Pd- Ni, Pd-Co, stable both in the liquid phase and in polymer matrices or in the adsorbed state on various carbon or silicon-containing supports.

The use of modern physicochemical methods (spectrophotometry, TLC, GC, HPLC, electron microscopy, FCC, NMR, alternating current polarography) to study the formation of nanoparticles, their stabilization in polymer matrices (cellophane, MEN-PPV, chitosan), size determination, and the shape of nanoparticles and ensembles made it possible to solve a number of significant fundamental and applied problems of modern nanotechnology. For the first time, for nanoparticles of metals, the prospects of using chromatography not only for detecting nanosized metal particles from micellar solutions but also for their separation into separate fractions (sieve (gel) chromatography) are shown. The results obtained are consistent with the sizes determined and controlled by the scale of the water pool diameter of the inverse micelles and the AFM data on nanostructure sizes.

It is of interest to investigate the effect of various nanoparticles of metals, carbon nanotubes, and SiO₂ nanoparticles on the optical properties (absorption and luminescence) of morphine solutions and the light-sensitive polymer MEN-PPV in the development of organic [solar energy](#) converters. Volt-ampere characteristics of the created composite photosensitive layers are measured. A relationship between the quenching of luminescence and an increase in photovoltaic characteristics is established.

Metal nanoparticles synthesized in inverse micelles find application in the manufacture of construction and finishing materials with bactericidal, anti-corrosive properties, in the creation of cartridges for water treatment of drinking water, materials for filtering and filtration, and catalysts and components with catalytic properties for solar and fuel cells.

In the development of nanocomposite materials with catalytic properties, the radiation-chemical approach to the modification of materials with small pores at the time of synthesis of nanoparticles of metals was first used in our country. Based on the highly porous polyurethane carrier and palladium nanoparticles, an active catalyst for the liquid phase process of methylation of aniline has been developed. Materials on the patenting of nanomaterials with specified properties are prepared based on the results of research work.

The field of application

The field of application of nanocomposites is very broad, from medicine to rocket and aircraft construction. Thermal insulation tiles for the reusable ship “Buran,” created by scientists of VIAM, are made of a nanocomposite based on silicon carbide. Very widely, nanocomposites are used in the production of American fighter-bombers of the 5th generation Lockheed Martin F-35 Lightning II. This is the first aircraft in which nanocomposites are used to manufacture body parts. The material based on nanocomposites from epoxy resin and nanotubes allowed designers to replace about one hundred other materials used earlier in the design of the hull of the aircraft.

Recently, nanocomposites have been widely used in dentistry for prosthetics. With the use of nanocomposites, artificial bone implants are grown. Modified nanocomposite polymers to create innovative packaging materials. The use of nanocomposites in the package reduces the amount of material used, reduces its overall cost, and strengthens the barrier properties of the package.

It is very promising to use composites based on carbon nanotubes and nanofibers. They can be used in catalysis, optoelectronics, and the manufacture of various sensors. Nanocomposites are great for immobilizing proteins, viruses, and bacteria. In the automotive industry, nano-clays have been used. They are used to increase the fire resistance, heat resistance, and wear resistance of various parts. These technologies were used in Audi A3, A4, and Volkswagen vans. Batteries based on silicon-carbon nanocomposites have excellent parameters: high capacitance and considerable current strength.

Packaging industry (high barrier films and PET- performs). The use of nanocomposites can reduce the number of layers of packaging, make it thinner, and replace expensive combined materials, while the packaging characteristics do not deteriorate [1].

- Automotive industry (plastics)
- Protection of main pipelines
- Aircraft construction
- Cable industry (incombustible cable compositions)

At present, most of the polymer nanocomposites are made by modified montmorillonite. The most popular and studied are polymer nanocomposites based on polyamide, polypropylene, polyethylene, polystyrene, and polyethylene terephthalate. The greatest demand for composites based on MMT is demonstrated by the packaging industry – 36%, significant [market shares are occupied by the electrical and automotive industries](#). The Russian market volume and 65% annual-growth figures were forecasts for 2010–2015; they should not be presented as current market results. In the Bryansk region, the production of nanomaterials based on large-tonnage polymers is being developed.



How Nanocomposites can help in automotive

The key role will be played precisely by the automobile industry, which accounts for about 70% of the consumption of polymer nanocomposite materials. Further growth in demand from this segment will be the main driver for the growth of the world market of polymer nanocomposites. Polymer composite materials are used in the automotive industry, usually for the production of such auto components and parts as handles and trim elements, rearview mirrors, Elements of a fuel tank, Suspension elements, Brake systems, and bumpers. Also, the report notes the expected growth in the segment, such as elastomeric nanocomposites, due to increased demand from tire manufacturers. The source projected that the automotive industry would remain the largest consumer during the five-year period covered by that report; "the next five years" is no longer a current forecast.



The growth of harmful emissions produced by road transport contributes to an increase in the temperature of the atmosphere and the deterioration of the ecological situation of the planet. At the same time, it is not possible to completely exclude these emissions, but they can be reduced to a minimum. Governments around the world are implementing stringent regulations and policies designed to reduce automobile emissions. Also, states and public organizations are actively working in the field of public awareness of the harmful effects of these pollutants on the environment and the atmosphere.

Automakers and representatives of related industries are shifting towards the more active use of electrical energy instead of energy derived from fossil fuels (oil, gas). Also, growth in demand for polymeric nanocomposites will be observed from other segments of consumption. The production of electronics and semiconductors, the creation of aerospace equipment, the military industry, the biomedical industry, construction, the packaging industry, and the renewable electric power industry will serve as additional (to the auto industry) and strong drivers of the rapid growth of the world market of polymer nanocomposites in the foreseeable future.

Conclusion

Nano-clays are widely used as fillers, and the demand for this material is anticipated to enhance in the foretell period. The spreading of clay in the polymer environment increases the exterior area. The 2% -8% nanocomposites in polymer clay meliorate the forcible and mechanically skillful, and it cuts down gas and moisture permeableness. Nano-clays provide such advantages as improving the life cycle of the product, reducing transportation costs due to light components, and reducing the need for flame retardants, which makes a reliable contribution to the growth of the global market for nanocomposites.

Works Cited

Choudhury, Kaushik Roy et al. "Solution-Processed Pentacene Quantum-Dot Polymeric Nanocomposite for Infrared Photodetection." *Applied Physics Letters* 89.5 (2006): n. pag. Web.

Gaharwar, Akhilesh K., Nicholas A. Peppas, and Ali Khademhosseini. "Nanocomposite Hydrogels for Biomedical Applications." *Biotechnology and Bioengineering* 111.3 (2014): 441-453. Web.

Kuznetsova, I. E., B. D. Zaitsev, and A. S. Kuznetsova. "Acoustic Waves in Structure 'piezoelectric Plate-Polymeric Nanocomposite Film.'" *Ultrasonics* 48.6-7 (2008): 587-590. Web.

Tollan, Christopher M. et al. "Irreversible Thermochromic Behavior in Gold and Silver Nanorod/Polymeric Ionic Liquid Nanocomposite Films." *ACS Applied Materials and Interfaces* 1.2 (2009): 348-352. Web.

Wang, Guang-Feng, Xiao-Ming Tao, and Rong-Xin Wang. "Flexible Organic Light-Emitting Diodes with a Polymeric Nanocomposite Anode." *Nanotechnology* 19.14 (2008): 145201. Web.

Yin, Jun, and Baolin Deng. "Polymer-Matrix Nanocomposite Membranes for Water Treatment." *Journal of Membrane Science* 2015: 256-275. Web.

Appendix

